



Visonic®

For a secure way of life

SMD-426 PG2 PowerG® Wireless Smoke Detector



Features & Benefits:

- PowerG two-way Frequency Hopping Spread Spectrum FHSS-TDMA technology - provides robustness and reliability closer than ever to wired
- Battery life 5-8 years with typical use, according to battery type
- Provides sound and transmitted alerts (for smoke, tamper, low battery)
- Loud (85db) alarm sound at 3m (10ft)
- Large transmission range enabling repeater-free installations
- Visible link quality indication shown on the device
- Simple wall or ceiling installation, with bracket
- Back tamper
- Fully certified by the most strict and demanding international standards such as EN 14604 for safety products in Europe, and designed to comply with UL 268 in the USA.

SMD-426 PG2 is a fully supervised wireless photoelectric smoke detector that is compatible with PowerMaster® wireless burglar alarm systems. Designed for a wide range of residential and commercial applications, this easily installed smoke detector has a streamlined design and an extended battery life for easy and low-cost maintenance.

Specifications:

Battery type:	3V, CR123A / CR17450 Lithium battery
Weight (including battery):	165g (5.8oz)
Operating temperature:	-10°C to 50°C (14°F to 122°F)
Operating environment:	Indoor
Dimensions:	120 X 58mm (4.7 X 2.3in)

Certifications:

